

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10242*00
Tyre Size	VF 900/60R42 NRO (SB)
Rec Rim	DW30B
Alternate Rim	-
NRO	DW28B
PR & LI/SI	189 D
Section Width (mm)	881
Overall Diameter (mm)	2147
Static Load Radius (mm)	979
Rolling Circumference (mm)	6421
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	5540	6470	7390	8320	10160	11330
25	5190	6060	6920	7790	9520	10610
30	5140	6000	6850	7710	9420	10510
40	5040	5880	6720	7560	9240	10300
50	5040	5880	6720	7560	9240	10300
65	5040	5880	6720	7560	9240	10300
70	4620	5390	6170	6940	8480	9450