

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10239*00
Tyre Size	VF 750/70R44 (SB)
Rec Rim	DW25B
Alternate Rim	–
NRO	–
PR & LI/SI	186 D
Section Width (mm)	742
Overall Diameter (mm)	2168
Static Load Radius (mm)	992
Rolling Circumference (mm)	6484
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2
10	5190	6050	6920	7790	9520	10450
25	4860	5670	6480	7290	8910	9790
30	4810	5610	6420	7220	8820	9690
40	4720	5500	6290	7080	8650	9500
50	4720	5500	6290	7080	8650	9500
65	4720	5500	6290	7080	8650	9500
70	4330	5050	5770	6500	7940	8720