

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	VF 380/95R38 NRO (SB)
Rec Rim	W13
Alternate Rim	W12
NRO	W12
PR & LI/SI	159 D
Section Width (mm)	383
Overall Diameter (mm)	1687
Static Load Radius (mm)	780
Rolling Circumference (mm)	5066
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4
10	2220	2600	2970	3340	4080	4480	4810
25	2080	2430	2780	3130	3820	4190	4510
30	2060	2410	2750	3100	3780	4150	4460
40	2020	2360	2700	3040	3710	4070	4375
50	2020	2360	2700	3040	3710	4070	4375
65	2020	2360	2700	3040	3710	4070	4375
70	1850	2170	2480	2790	3400	3730	4010