

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*9028*00
Tyre Size	VF 380/85R46 NRO (SB)
Rec Rim	W13
Alternate Rim	DW12,W12,DW13
NRO	W12
PR & LI/SI	162 D
Section Width (mm)	383
Overall Diameter (mm)	1814
Static Load Radius (mm)	851
Rolling Circumference (mm)	5447
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4	2.8
10	2240	2620	2990	3370	4110	4520	4820	5230
25	2100	2450	2800	3150	3850	4230	4510	4890
30	2080	2430	2770	3120	3810	4190	4470	4850
40	2040	2380	2720	3060	3740	4110	4380	4750
50	2040	2380	2720	3060	3740	4110	4380	4750
65	2040	2380	2720	3060	3740	4110	4380	4750
70	1870	2180	2500	2810	3430	3770	4020	4360