

VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

Salient Features & Benefits

VF Drive Radial 2000, specially designed Ultra Modern Tractor.

Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*9031*00
Tyre Size	VF 480/80R46 (SB)
Rec Rim	DW16L
Alternate Rim	DW15L
NRO	–
PR & LI/SI	177 D
Section Width (mm)	479
Overall Diameter (mm)	1936
Static Load Radius (mm)	901
Rolling Circumference (mm)	5814
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4	2.8	3.2	3.6
10	3010	3510	4020	4520	5520	6060	6450	7070	7620	8030
25	2820	3290	3760	4230	5170	5680	6040	6620	7140	7520
30	2790	3250	3720	4190	5120	5620	5980	6560	7070	7450
40	2740	3190	3650	4110	5020	5510	5860	6430	6930	7300
50	2740	3190	3650	4110	5020	5510	5860	6430	6930	7300
65	2740	3190	3650	4110	5020	5510	5860	6430	6930	7300
70	2510	2930	3350	3770	4610	5060	5380	5900	6360	6700