

## VDR 900 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years



### Salient Features & Benefits

#### VF Drive Radial 900, specially designed Self-Propelled Sprayer.

##### Soil Protection

- VF - Very High Flexion tyre with strong lugs
- Carries same loads at 40% less pressure than standard radial tyre.

##### Excellent traction with self-cleaning characteristics

- Stronger lugs with larger Contact Patch equipped with unique mud breaker.
- Decreases slippage, delivers lower fuel consumption, and increases overall productivity.

##### Higher Load Capacity

- Extra Strong Casing Equipped with Steel belts
- Higher load-carrying capacity in all applications & Improved Puncture resistance.

##### Stability and Smooth Ride

- High number of lug with optimized lug over lap.
- Comfortable ride on hard surfaces & soft conditions.


##### Longer Tyre Life

- Advance rubber compound.
- Reduces tread wear and extends the overall service life of the tyre.

## Machineries



Tractor



Self Propelled Sprayer

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	VF 480/95R50 (SB)
Rec Rim	DW16L
Alternate Rim	DW15L
PR & LI/SI	176 D
Section Width (mm)	479
Overall Diameter (mm)	2182
Static Load Radius (mm)	1011
Rolling Circumference (mm)	6552
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	1	1.6	2	2.4
10	4830	6640	7290	7810
25	4520	6220	6830	7310
30	4480	6160	6760	7240
40	4390	6040	6630	7100
50	4390	6040	6630	7100
65	4390	6040	6630	7100