

VDR 900 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years



Salient Features & Benefits

VF Drive Radial 900, specially designed Self-Propelled Sprayer.

Soil Protection

- VF - Very High Flexion tyre with strong lugs
- Carries same loads at 40% less pressure than standard radial tyre.

Excellent traction with self-cleaning characteristics

- Stronger lugs with larger Contact Patch equipped with unique mud breaker.
- Decreases slippage, delivers lower fuel consumption, and increases overall productivity.

Higher Load Capacity

- Extra Strong Casing Equipped with Steel belts
- Higher load-carrying capacity in all applications & Improved Puncture resistance.

Stability and Smooth Ride

- High number of lug with optimized lug over lap.
- Comfortable ride on hard surfaces & soft conditions.


Longer Tyre Life

- Advance rubber compound.
- Reduces tread wear and extends the overall service life of the tyre.

Machineries



Tractor



Self Propelled Sprayer

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10604*00
Tyre Size	VF 250/115R54 (SB)
Rec Rim	W8
Alternate Rim	-
PR & LI/SI	151 D
Section Width (mm)	250
Overall Diameter (mm)	1947
Static Load Radius (mm)	923
Rolling Circumference (mm)	5847
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	1	1.6	2	2.4	2.6
10	2240	3080	3390	3610	3800
25	2100	2880	3170	3380	3550
30	2080	2860	3140	3350	3520
40	2040	2800	3080	3280	3450
50	2040	2800	3080	3280	3450
65	2040	2800	3080	3280	3450