

## VDR 2000 - Technical Specifications

Agriculture | Radial | R-1W | TL | 7 Years

### Salient Features & Benefits

### VF Drive Radial 2000, specially designed Ultra Modern Tractor.

#### Outstanding Traction & Stability

- Advanced Tread design.
- More Gripping Edge and ensuring better control in various terrains, even in wet and muddy conditions.

#### Reduced Soil Compaction

- Wider and Longer Footprint
- Reduce Soil stress, compaction resulting in more yield.

#### Increased Fuel Efficiency

- Lower rolling resistance
- Helps save fuel, cutting down operational costs.

#### Higher Load Capacity

- Advance VF technology Strong shoulder with higher draft angle and base radius.
- Carry 40% more weight at the same pressure as standard radial tyres.

#### Durability and Strength

- Strong Casing with High Performance Steel belts.
- Offers better impact resistance and defend against stubble to enhance tyre more durable.

#### Longer Tyre Life


- Engineered with advanced rubber compound.
- Even wear both on the road and in the field.

#### NRO (Narrow Rim Option)

- NRO marking on sidewall permitted by standard.
- It is possible to mount both standard and narrow rim.



## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*9032*00
Tyre Size	VF 480/95R54 NRO (SB)
Rec Rim	DW16L
Alternate Rim	DW15L
NRO	DW15L
PR & LI/SI	180 D
Section Width (mm)	479
Overall Diameter (mm)	2284
Static Load Radius (mm)	1062
Rolling Circumference (mm)	6859
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.6	0.8	1	1.2	1.6	2	2.4	2.8
10	3760	4400	5030	5650	6910	7580	8070	8800
25	3520	4120	4710	5290	6470	7100	7560	8240
30	3490	4080	4660	5240	6410	7030	7490	8160
40	3420	4000	4570	5140	6280	6890	7340	8000
50	3420	4000	4570	5140	6280	6890	7340	8000
65	3420	4000	4570	5140	6280	6890	7340	8000
70	3140	3670	4190	4720	5760	6320	6730	7340