



FTB 190 - Technical Specifications

Agriculture | Bias | I-3 | TL | 5 Years

Salient Features & Benefits

Flotation Tyre bias 190, specially designed for Trailer

Excellent Traction

- Flotation tread design
- Particularly suitable for field and road transport as well as for spreading operations.

Reduced Soil Compaction

- Larger inner volumes with Wider footprint.
- Ensure low soil compaction, minimizes crop damage.

Good Roadability

- Wider center block and low lug angles
- Smooth ride on road as well as in field provides uniform wear.

Excellent Durability

- Super Strong Casing with High Flex cracking & Abrasion resistance Tread compound.
- High load carrying capacity & Offers superior resistance to wear and tear in all surfaces Ensures Longer Life.



Machineries



Tanker



Flotation Trailer

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	300/65-12
Rec Rim	9
Alternate Rim	-
PR & LI/SI	8 PR 122A8 FR 110AB DW
Section Width (mm)	295
Overall Diameter (mm)	680
Static Load Radius (mm)	307
Rolling Circumference (mm)	2042
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2.8	3	3.2	3.6
10	1430	1480	1540	1650
25	1210	1260	1310	1400
40	1020	1060	1100	1180
50	920	950	990	1060

Free rolling

km/h / bar	2.8	3	3.2	3.6
10	2020	2100	2180	2340
25	1710	1790	1860	1990
40	1440	1500	1560	1670
50	1300	1350	1400	1500