

IMB 164 - Technical Specifications

Agriculture | Bias | IMP | TT/TL | 5 Years



Salient Features & Benefits

IMB 164, specially designed for implements

High Load Carrying Capacity

- Reinforced nylon carcass
- Built to carry heavy loads during agricultural and transport operations without compromising stability

Low Soil Protection

- Specially designed ribbed tread with wider footprint
- Reduces soil disturbance and ensures minimal compaction in field use

Durability & Long Tyre Life

- High rubber content and wear-resistant compound
- Ensures extended tyre life, even in demanding haulage and off-road conditions

Versatile Application

- On- and off-road compatible rib pattern
- Offers reliable performance across fields, paved roads, and mixed terrain

Machineries



Implement

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	250/65-14.5
Rec Rim	AG 8.00
Alternate Rim	-
PR & LI/SI	12 PR 119 A8
Section Width (mm)	251
Overall Diameter (mm)	694
Static Load Radius (mm)	318
Rolling Circumference (mm)	2076
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Free rolling

km/h / bar	3.6	3.9	4.3	4.7
10	1620	1710	1810	1900
25	1380	1450	1540	1620
30	1300	1370	1440	1520
40	1160	1220	1290	1360