



## IMR 140 - Technical Specifications

Agriculture | Radial | IMP | TL | 7 Years



### Salient Features & Benefits

**IMR 140, Specially designed for Implements with superior grip and stability**

#### Low Soil Compaction

- Wide footprint with optimised shoulder lugs
- Protects soil structure and preserves grassland health

#### Superior Traction

- Specially engineered tread pattern
- Delivers strong grip on soft or inclined surfaces

#### Excellent Self-Cleaning

- Open lug spacing and tread channelling
- Ejects mud and debris efficiently for uninterrupted field use

#### Enhanced Lateral Stability

- Reinforced casing construction
- Maintains control and balance, even on slopes and uneven terrain

#### Long-Lasting Performance

- Wear-resistant tread compound
- Stands up to regular field work with longer tyre life

## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*7597*00
Tyre Size	33X15.50R15
Rec Rim	13LB
Alternate Rim	-
PR & LI/SI	126 B
Section Width (mm)	391
Overall Diameter (mm)	843
Static Load Radius (mm)	381
Rolling Circumference (mm)	2521
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar		3.2
50		1700