

IMB 160 - Technical Specifications

Agriculture | Bias | I-1 | TT/TL | 5 Years

Salient Features & Benefits

Implement Bias 160, specially designed for Implements

Low Soil Compaction

- Wider footprint with soil-friendly tread design
- Minimises soil compaction and protects grassland and sensitive soil

High Load Carrying Capacity

- Strong nylon carcass
- Withstands heavy loads during implement and transport operations

Improved Stability

- Optimised height-to-width ratio
- Enhances implement stability, even on uneven terrain

Smooth On-Road & Off-Road Ride

- Central rib with shoulder lug configuration
- Provides better ride comfort and handling on both road and field surfaces

Excellent Durability:

- High Flex cracking & Abrasion resistance Tread compound.
- Offers superior resistance to wear and tear in all surfaces
Ensures Longer Life



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7816*00
Tyre Size	10.0/75-15.3 (260/75-15.3)
Rec Rim	9
Alternate Rim	-
PR & LI/SI	18 PR 135A8 FR 122A8 DW
Section Width (mm)	264
Overall Diameter (mm)	760
Static Load Radius (mm)	348
Rolling Circumference (mm)	2274
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Free rolling

km/h / bar	7.1
10	3050
25	2590
30	2440
40	2180
50	1960

Drive Wheel

km/h / bar	7.1
10	2100
25	1790
30	1680
40	1500
50	1350