



FTB 190 - Technical Specifications

Agriculture | Bias | I-3 | TL | 5 Years

Salient Features & Benefits

Flotation Tyre bias 190, specially designed for Trailer

Excellent Traction

- Flotation tread design
- Particularly suitable for field and road transport as well as for spreading operations.

Reduced Soil Compaction

- Larger inner volumes with Wider footprint.
- Ensure low soil compaction, minimizes crop damage.

Good Roadability

- Wider center block and low lug angles
- Smooth ride on road as well as in field provides uniform wear.

Excellent Durability

- Super Strong Casing with High Flex cracking & Abrasion resistance Tread compound.
- High load carrying capacity & Offers superior resistance to wear and tear in all surfaces Ensures Longer Life.



Machineries



Tanker



Flotation Trailer

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6591*00
Tyre Size	400/60-15.5
Rec Rim	AG13.00
Alternate Rim	-
PR & LI/SI	14 PR 145 A8 FR 141 B FR 132 A8 DW 128 B DW
Section Width (mm)	404
Overall Diameter (mm)	874
Static Load Radius (mm)	395
Rolling Circumference (mm)	2625
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2.7	3	3.3	3.6
10	2370	2520	2660	2800
25	2010	2140	2260	2380
40	1690	1800	1900	2000
50	1521	1620	1710	1800

Free rolling

km/h / bar	2.7	3	3.3	3.6
10	3430	3650	3860	4060
25	2920	3110	3280	3450
40	2450	2610	2760	2900
50	2210	2350	2480	2610