



FFB 843 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

FFB 843- High Flotation Design with Enhanced Strength & Field Protection

Flotation Tread Design:

- Excellent Traction.
- Better Self Cleaning.

Strong Nylon Carcass:

- High Load Carrying Capacity.

Overlap of lugs at centre:

- Provided good Roadability.
- Low Tread wear.
- Smooth Ride.

Optimized Bead Area:

- Minimizes Bead failure in operation.
- Ease of mounting.
- Resistance to Rim slip.

SSR compound (Special Stubble Resistant):

- Longer Tire Life and defense against stubble which provides better protection on field.

Reinforced Steel belts:

- Increased resistance to punctures and a high carrying capacity.



Machineries



Forestry Forwarder Forestry Harvester

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/21*10864*00
Tyre Size	400/60-15.5 (SB)
Rec Rim	AG 13.00
Alternate Rim	-
PR & LI/SI	20 PR 152 A8 / 148 B FR 140 A8 / 135 B DW
Section Width (mm)	404
Overall Diameter (mm)	874
Static Load Radius (mm)	395
Rolling Circumference (mm)	2625
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	3.7	4.1	4.5	5
10	2940	3120	3290	3500
25	2500	2650	2800	2980
30	2350	2500	2630	2800
40	2100	2230	2350	2500
50	1890	2010	2120	2250

Free rolling

km/h / bar	3.7	4.1	4.5	5
10	4170	4420	4680	4970
25	3550	3760	3970	4220
30	3340	3540	3740	3980
40	2980	3160	3340	3550
50	2680	2840	3010	3200