

IMB 160 - Technical Specifications

Agriculture | Bias | I-1 | TT/TL | 5 Years

Salient Features & Benefits

Implement Bias 160, specially designed for Implements

Low Soil Compaction

- Wider footprint with soil-friendly tread design
- Minimises soil compaction and protects grassland and sensitive soil

High Load Carrying Capacity

- Strong nylon carcass
- Withstands heavy loads during implement and transport operations

Improved Stability

- Optimised height-to-width ratio
- Enhances implement stability, even on uneven terrain

Smooth On-Road & Off-Road Ride

- Central rib with shoulder lug configuration
- Provides better ride comfort and handling on both road and field surfaces

Excellent Durability:

- High Flex cracking & Abrasion resistance Tread compound.
- Offers superior resistance to wear and tear in all surfaces
Ensures Longer Life



Machineries



Implement

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7223*00
Tyre Size	13.0/75-16
Rec Rim	11
Alternate Rim	-
PR & LI/SI	12 PR 138A8 FR
Section Width (mm)	336
Overall Diameter (mm)	900
Static Load Radius (mm)	407
Rolling Circumference (mm)	2692
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Free rolling

km/h / bar	4
10	3300
25	2780
30	2640
40	2360
50	2120