

FTB 190 - Technical Specifications

Agriculture | Bias | I-3 | TL | 5 Years



Salient Features & Benefits

Flotation Tyre bias 190, specially designed for Trailer

Excellent Traction

- Flotation tread design
- Particularly suitable for field and road transport as well as for spreading operations.

Reduced Soil Compaction

- Larger inner volumes with Wider footprint.
- Ensure low soil compaction, minimizes crop damage.

Good Roadability

- Wider center block and low lug angles
- Smooth ride on road as well as in field provides uniform wear.

Excellent Durability

- Super Strong Casing with High Flex cracking & Abrasion resistance Tread compound.
- High load carrying capacity & Offers superior resistance to wear and tear in all surfaces Ensures Longer Life.

Machineries



Tanker



Flotation Trailer

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7226
Tyre Size	400/55-22.5
Rec Rim	13
Alternate Rim	-
PR & LI/SI	14PR 150 A8 FR 146 B FR 138A8 DW 134 B DW
Section Width (mm)	404
Overall Diameter (mm)	1020
Static Load Radius (mm)	471
Rolling Circumference (mm)	3063
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2.3	2.5
10	2830	2970
25	2400	2520
40	2020	2120
50	1818	1908

Free rolling

km/h / bar	2.3	2.5
10	4020	4210
25	3420	3580
40	2870	3010
50	2580	2710