

FFB 843 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

FFB 843- High Flotation Design with Enhanced Strength & Field Protection

Flotation Tread Design:

- Excellent Traction.
- Better Self Cleaning.

Strong Nylon Carcass:

- High Load Carrying Capacity.

Overlap of lugs at centre:

- Provided good Roadability.
- Low Tread wear.
- Smooth Ride.

Optimized Bead Area:

- Minimizes Bead failure in operation.
- Ease of mounting.
- Resistance to Rim slip.

SSR compound (Special Stubble Resistant):

- Longer Tire Life and defense against stubble which provides better protection on field.

Reinforced Steel belts:

- Increased resistance to punctures and a high carrying capacity.



Machineries



Forestry Forwarder Forestry Harvester

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	400/60-22.5 (5B)
Rec Rim	13
Alternate Rim	-
PR & LI/SI	20 PR FR-163 A8 159 B DW-151 A8 147 B
Section Width (mm)	407
Overall Diameter (mm)	1070
Static Load Radius (mm)	491.4
Rolling Circumference (mm)	3213.1
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	5
10	4830
25	4110
30	3860
40	3450
50	3110

Free rolling

km/h / bar	5
10	6830
25	5800
30	5460
40	4875
50	4390