

FFB 841 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

Forestry forwarder Bias 841 Engineered for advanced forestry applications which is Track tyre for harvesters and forwarders



Track Compatibility with High Stability

- Superior tread geometry with inter-lug terraces & centre tie bar
- Provides excellent grip and stability even with track usage; minimises lug movement for smooth operation

Exceptional Puncture Resistance

- Reinforced steel-belted carcass with protective forestry compound
- Protects against sharp stumps, stones, and reduces downtime in harsh forestry environments

Heavy Load Handling

- Robust sidewall equipped with strong lug base and reinforced bead zone
- Withstands heavy loads and prevents rim slippage

Strong Lug Base:

- Design with Centre Tie Bar.
- Minimizes lug shuffling in operation.

Machineries



Forestry Forwarder



Forestry Harvester

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10683*00
Tyre Size	710/40-22.5 (SB)
Rec Rim	AG24.00
Alternate Rim	-
PR & LI/SI	24PR 167A8
Section Width (mm)	709
Overall Diameter (mm)	1167
Static Load Radius (mm)	531
Rolling Circumference (mm)	3504
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Forestry Service (LT)

km/h / bar	6
10	6700

Road Application

km/h / bar	6
20	6700
30	5830
40	5450

Skidder Service (HT)

km/h / bar	6
10	5450