



FTR 170 - Technical Specifications

Agriculture | Radial | IMP | TL | 7 Years

Salient Features & Benefits

Flotation Radial 170 for On Road & Farm Trailer Application.

Excellent Grip

- Special Homogenous Directional Tread design.
- Enhanced Traction & Superior Self-Cleaning Capability

Durability and Strength

- Reinforced Steel Belts & Bead area Design for heavy loads and rough conditions.
- Excellent resistance to punctures, High load carrying capacity, & Protection against bead damage.

Soil Protection

- Larger footprint with uniform pressure distribution
- Reduces soil compaction & increases crop yield.

Save Fuel


- Low Rolling resistance
- Decreased fuel consumption

Excellent Stability

- Uniform load distribution.
- Riding comfort & smoother ride over rough or uneven terrain.



Machineries



Tanker



Flotation Trailer

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/21*10610*00
Tyre Size	600/55R22.5 (5B)
Rec Rim	AG20.00
Alternate Rim	-
PR & LI/SI	162 D
Section Width (mm)	611
Overall Diameter (mm)	1232
Static Load Radius (mm)	558
Rolling Circumference (mm)	3685
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	1	1.2	1.6	2	2.4	2.8	3.2	3.6	4
Static	4000	4510	5500	6300	7270	8260	9060	9960	10930

Mixed Application

km/h / bar	1	1.2	1.6	2	2.4	2.8	3.2	3.6	4
10	3130	3530	4300	4930	5690	6460	7090	7790	8550
25	2750	3100	3780	4330	4990	5670	6230	6840	7510
30	2630	2960	3610	4140	4770	5420	5950	6540	7170
40	2370	2670	3250	3730	4300	4880	5360	5890	6460
50	2110	2370	2890	3320	3820	4340	4770	5240	5750
65	1740	1960	2390	2740	3160	3590	3940	4330	4750