

## FFB 840 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

### Salient Features & Benefits

**Forestry forwarder Bias 840 which is Traction tyre for harvesters and forwarders**

#### Outstanding Grip

- High lug angle with extensive inter-lug space .
- Provides excellent traction in operation & Better Self-cleaning.

#### Easy of Track fitment

- Optimized tread design
- When the terrain does not require tracks you can omit them, but it is possible to put them on for more demanding situation.

#### Low ground pressure with Drive comfort

- Wider Footprint
- Large tread width contributes to low soil compaction and driver comfort.

#### Less Breakdown in severe forest application

- Protective forestry compound
- Resistance from frequent punctures & cuts.

#### Easy of tyre fitment


- Reinforced bead with optimized bead profile.
- Easy of mounting & without any rim slippage in operation.

#### Outstanding stability

- Strong Casing with High Performance Steel belts.
- Less impact and fatigue failure with High load carrying capacity



## Machineries



Forestry Forwarder   Forestry Harvester

**Standard:** International Standards

## Dimensions International Standards

ECE	E11*106R00/19*7819*00
Tyre Size	710/40-22.5 (SB)
Rec Rim	AG24.00
Alternate Rim	-
PR & LI/SI	20PR 161A8 HT -161A2 LT -168A2
Section Width (mm)	705
Overall Diameter (mm)	1170
Static Load Radius (mm)	533
Rolling Circumference (mm)	3513
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

## Forestry Service (LT)

km/h / bar	5
10	5600

## Road Application

km/h / bar	5
20	5690
30	4950
40	4625

## Skidder Service (HT)

km/h / bar	5
10	4625