



FTB 190 - Technical Specifications

Agriculture | Bias | I-3 | TL | 5 Years

Salient Features & Benefits

Flotation Tyre bias 190, specially designed for Trailer

Excellent Traction

- Flotation tread design
- Particularly suitable for field and road transport as well as for spreading operations.

Reduced Soil Compaction

- Larger inner volumes with Wider footprint.
- Ensure low soil compaction, minimizes crop damage.

Good Roadability


- Wider center block and low lug angles
- Smooth ride on road as well as in field provides uniform wear.

Excellent Durability

- Super Strong Casing with High Flex cracking & Abrasion resistance Tread compound.
- High load carrying capacity & Offers superior resistance to wear and tear in all surfaces Ensures Longer Life.



Machineries



Tanker



Flotation Trailer

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7007*00
Tyre Size	600/55-26.5
Rec Rim	20
Alternate Rim	-
PR & LI/SI	16 PR 170 A8 FR 167 B FR 159 A8 DW 156 B DW
Section Width (mm)	611
Overall Diameter (mm)	1333
Static Load Radius (mm)	609
Rolling Circumference (mm)	3987
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2	2.2	2.4	2.6
10	5250	5540	5840	6130
25	4460	4710	4960	5210
40	3750	3960	4170	4375
50	3375	3564	3753	3938

Free rolling

km/h / bar	2	2.2	2.4	2.6
10	7210	7630	8020	8400
25	6130	6490	6820	7140
40	5150	5450	5730	6000
50	4640	4910	5160	5400