

FFB 840 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

Forestry forwarder Bias 840 which is Traction tyre for harvesters and forwarders

Outstanding Grip

- High lug angle with extensive inter-lug space .
- Provides excellent traction in operation & Better Self-cleaning.

Easy of Track fitment

- Optimized tread design
- When the terrain does not require tracks you can omit them, but it is possible to put them on for more demanding situation.

Low ground pressure with Drive comfort

- Wider Footprint
- Large tread width contributes to low soil compaction and driver comfort.

Less Breakdown in severe forest application

- Protective forestry compound
- Resistance from frequent punctures & cuts.

Easy of tyre fitment

- Reinforced bead with optimized bead profile.
- Easy of mounting & without any rim slippage in operation.

Outstanding stability

- Strong Casing with High Performance Steel belts.
- Less impact and fatigue failure with High load carrying capacity



Machineries



Forestry Forwarder



Forestry Harvester

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7623*00
Tyre Size	600/55-26.5 (SB)
Rec Rim	AG20.00
Alternate Rim	-
PR & LI/SI	20PR 165A8 HT -165A2 LT -172A2
Section Width (mm)	600
Overall Diameter (mm)	1345
Static Load Radius (mm)	614
Rolling Circumference (mm)	4039
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Forestry Service (LT)

km/h / bar	5
10	6300

Road Application

km/h / bar	5
20	6330
30	5510
40	5150

Skidder Service (HT)

km/h / bar	5
10	5150