

## FTR 170 - Technical Specifications

Agriculture | Radial | IMP | TL | 7 Years



### Salient Features & Benefits

#### Flotation Radial 170 for On Road & Farm Trailer Application.

##### Excellent Grip

- Special Homogenous Directional Tread design.
- Enhanced Traction & Superior Self-Cleaning Capability

##### Durability and Strength

- Reinforced Steel Belts & Bead area Design for heavy loads and rough conditions.
- Excellent resistance to punctures, High load carrying capacity, & Protection against bead damage.

##### Soil Protection

- Larger footprint with uniform pressure distribution
- Reduces soil compaction & increases crop yield.


##### Save Fuel

- Low Rolling resistance
- Decreased fuel consumption

##### Excellent Stability

- Uniform load distribution.
- Riding comfort & smoother ride over rough or uneven terrain.

## Machineries



Tanker



Flotation Trailer

**Standard:** International Standards

## Dimensions International Standards

ECE	E11*106R00/20*7806*00
Tyre Size	650/60R26.5 (SB)
Rec Rim	AG20.00
Alternate Rim	-
PR & LI/SI	180 D
Section Width (mm)	655
Overall Diameter (mm)	1450
Static Load Radius (mm)	657
Rolling Circumference (mm)	4354
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

## Load Capacity

km/h / bar	1	1.2	1.5	2	2.8	3.2	3.6	4	5	6
Static	5240	5910	6900	8260	10810	11890	13040	14280	16080	18400

## Mixed Application

km/h / bar	1	1.2	1.5	2	2.8	3.2	3.6	4	5	6
10	4100	4630	5400	6460	8460	9310	10210	11180	12580	14400
25	3600	4060	4740	5670	7430	8170	8960	9810	11040	12640
30	3440	3880	4530	5420	7100	7810	8560	9380	10550	12080
40	3100	3500	4080	4880	6390	7030	7710	8450	9510	10880
50	2760	3110	3630	4340	5690	6260	6860	7510	8460	9680
65	2280	2570	3000	3590	4700	5170	5670	6210	6990	8000