

FFB 840 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

Forestry forwarder Bias 840 which is Traction tyre for harvesters and forwarders

Outstanding Grip

- High lug angle with extensive inter-lug space .
- Provides excellent traction in operation & Better Self-cleaning.

Easy of Track fitment

- Optimized tread design
- When the terrain does not require tracks you can omit them, but it is possible to put them on for more demanding situation.

Low ground pressure with Drive comfort

- Wider Footprint
- Large tread width contributes to low soil compaction and driver comfort.

Less Breakdown in severe forest application

- Protective forestry compound
- Resistance from frequent punctures & cuts.

Easy of tyre fitment

- Reinforced bead with optimized bead profile.
- Easy of mounting & without any rim slippage in operation.

Outstanding stability

- Strong Casing with High Performance Steel belts.
- Less impact and fatigue failure with High load carrying capacity



Machineries



Forestry Forwarder Forestry Harvester

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	750/55-26.5 (SB)
Rec Rim	AG24.00
Alternate Rim	-
PR & LI/SI	24PR 182A8
Section Width (mm)	755
Overall Diameter (mm)	1480
Static Load Radius (mm)	669
Rolling Circumference (mm)	4444
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Forestry Service (LT)

km/h / bar	6
10	10300

Road Application

km/h / bar	6
20	10460
30	9100
40	8500

Skidder Service (HT)

km/h / bar	6
10	8500