

## FFB 841 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

### Salient Features & Benefits

**Forestry forwarder Bias 841 Engineered for advanced forestry applications which is Track tyre for harvesters and forwarders**



### Track Compatibility with High Stability

- Superior tread geometry with inter-lug terraces & centre tie bar
- Provides excellent grip and stability even with track usage; minimises lug movement for smooth operation

### Exceptional Puncture Resistance

- Reinforced steel-belted carcass with protective forestry compound
- Protects against sharp stumps, stones, and reduces downtime in harsh forestry environments


### Heavy Load Handling

- Robust sidewall equipped with strong lug base and reinforced bead zone
- Withstands heavy loads and prevents rim slippage

### Strong Lug Base:

- Design with Centre Tie Bar.
- Minimizes lug shuffling in operation.

## Machineries



Forestry Forwarder   Forestry Harvester

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	710/45-26.5 (SB)
Rec Rim	AG24.00
Alternate Rim	-
PR & LI/SI	20PR 168 A8
Section Width (mm)	705
Overall Diameter (mm)	1345
Static Load Radius (mm)	614
Rolling Circumference (mm)	4039
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Forestry Service (LT)

km/h / bar	5.5
10	6900

### Road Application

km/h / bar	5.5
20	6890
30	5990
40	5600

### Skidder Service (HT)

km/h / bar	5.5
10	5600