

## FFB 840 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

### Salient Features & Benefits

### Forestry forwarder Bias 840 which is Traction tyre for harvesters and forwarders

#### Outstanding Grip

- High lug angle with extensive inter-lug space .
- Provides excellent traction in operation & Better Self-cleaning.

#### Easy of Track fitment

- Optimized tread design
- When the terrain does not require tracks you can omit them, but it is possible to put them on for more demanding situation.

#### Low ground pressure with Drive comfort

- Wider Footprint
- Large tread width contributes to low soil compaction and driver comfort.

#### Less Breakdown in severe forest application

- Protective forestry compound
- Resistance from frequent punctures & cuts.

#### Easy of tyre fitment

- Reinforced bead with optimized bead profile.
- Easy of mounting & without any rim slippage in operation.

#### Outstanding stability

- Strong Casing with High Performance Steel belts.
- Less impact and fatigue failure with High load carrying capacity



## Machineries



Forestry Forwarder   Forestry Harvester

**Standard:** ProductComponent.International Standards

## Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	600/55-26.5 (SB)
Rec Rim	AG20.00
Alternate Rim	-
PR & LI/SI	24PR 170A8 HT-170A2 LT-177A2
Section Width (mm)	611
Overall Diameter (mm)	1345
Static Load Radius (mm)	614
Rolling Circumference (mm)	4039
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

## Forestry Service (LT)

km/h / bar	6
10	7300

## Road Application

km/h / bar	6
20	7380
30	6420
40	6000

## Skidder Service (HT)

km/h / bar	6
10	6000