



## FFB 842 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

### Salient Features & Benefits

### Forestry forwarder Bias 842 which is Traction tyre for harvesters and forwarders

#### High Traction:

- Optimized lug angle with extensive inter-lug space.
- Provides excellent traction in operation & Better Self-cleaning.

#### Less Breakdown in severe forest application

- Protective forestry compound
- Resistance from frequent punctures & cuts.

#### Outstanding stability

- Strong Casing with High Performance Steel belts.
- Less impact and fatigue failure with High load carrying capacity

#### Fuel Efficiency and Reduced Vibration

- Dense Tread Mass with Improved Lug Overlap.
- Minimizes vibration for superior ride comfort while improving

#### Exceptional Puncture Resistance:

- Reinforced steel-belted carcass with protective forestry compound
- Protects against sharp stumps, stones, and reduces downtime in harsh forestry environments.



## Machineries



Forestry Forwarder

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	800/45-30.5 (SB)
Rec Rim	AG28.00
Alternate Rim	-
PR & LI/SI	20PR 174A8/181A2
Section Width (mm)	800
Overall Diameter (mm)	1505
Static Load Radius (mm)	689
Rolling Circumference (mm)	4519
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Forestry Service (LT)

km/h / bar	3.4
10	8250

### Road Application

km/h / bar	3.4
20	8240
30	7170
40	6700

### Skidder Service (HT)

km/h / bar	3.4
10	6700