



FTR 170 - Technical Specifications

Agriculture | Radial | IMP | TL | 7 Years

Salient Features & Benefits

Flotation Radial 170 for On Road & Farm Trailer Application.

Excellent Grip

- Special Homogenous Directional Tread design.
- Enhanced Traction & Superior Self-Cleaning Capability

Durability and Strength

- Reinforced Steel Belts & Bead area Design for heavy loads and rough conditions.
- Excellent resistance to punctures, High load carrying capacity, & Protection against bead damage.

Soil Protection

- Larger footprint with uniform pressure distribution
- Reduces soil compaction & increases crop yield.

Save Fuel

- Low Rolling resistance
- Decreased fuel consumption

Excellent Stability

- Uniform load distribution.
- Riding comfort & smoother ride over rough or uneven terrain.



Machineries



Tanker



Flotation Trailer

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*10353*00
Tyre Size	800/60R32 (SB)
Rec Rim	DW27B
Alternate Rim	-
PR & LI/SI	185 D
Section Width (mm)	818
Overall Diameter (mm)	1773
Static Load Radius (mm)	802
Rolling Circumference (mm)	5303
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	1.2	1.6	2	2.4	2.8	3.2	3.6	4
Static	8900	10880	12470	14380	16310	17920	19690	21280

Mixed Application

km/h / bar	1.2	1.6	2	2.4	2.8	3.2	3.6	4
10	6970	8510	9760	11250	12760	14020	15410	16650
25	6110	7470	8560	9880	11200	12310	13520	14620
30	5840	7140	8180	9440	10710	11760	12930	13970
40	5260	6430	7370	8500	9640	10590	11640	12580
50	4680	5720	6560	7560	8580	9430	10360	11190
65	3870	4730	5420	6250	7090	7790	8560	9250