

## FFB 840 - Technical Specifications

Forestry | Bias | LS-2 | TL | 5 Years

### Salient Features & Benefits

### Forestry forwarder Bias 840 which is Traction tyre for harvesters and forwarders

#### Outstanding Grip

- High lug angle with extensive inter-lug space .
- Provides excellent traction in operation & Better Self-cleaning.

#### Easy of Track fitment

- Optimized tread design
- When the terrain does not require tracks you can omit them, but it is possible to put them on for more demanding situation.

#### Low ground pressure with Drive comfort

- Wider Footprint
- Large tread width contributes to low soil compaction and driver comfort.

#### Less Breakdown in severe forest application

- Protective forestry compound
- Resistance from frequent punctures & cuts.

#### Easy of tyre fitment

- Reinforced bead with optimized bead profile.
- Easy of mounting & without any rim slippage in operation.

#### Outstanding stability

- Strong Casing with High Performance Steel belts.
- Less impact and fatigue failure with High load carrying capacity



## Machineries



Forestry Forwarder   Forestry Harvester

**Standard:** ProductComponent.International Standards

## Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	780/50-28.5 (SB)
Rec Rim	AG26.00
Alternate Rim	-
PR & LI/SI	26PR 185A8
Section Width (mm)	782
Overall Diameter (mm)	1515
Static Load Radius (mm)	688.3
Rolling Circumference (mm)	4549.4
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

## Forestry Service (LT)

km/h / bar	6.5
10	11500

## Road Application

km/h / bar	6.5
20	11380
30	9900
40	9250

## Skidder Service (HT)

km/h / bar	6.5
10	9250