



FTR 170 - Technical Specifications

Agriculture | Radial | IMP | TL | 7 Years

Salient Features & Benefits

Flotation Radial 170 for On Road & Farm Trailer Application.

Excellent Grip

- Special Homogenous Directional Tread design.
- Enhanced Traction & Superior Self-Cleaning Capability

Durability and Strength

- Reinforced Steel Belts & Bead area Design for heavy loads and rough conditions.
- Excellent resistance to punctures, High load carrying capacity, & Protection against bead damage.

Soil Protection

- Larger footprint with uniform pressure distribution
- Reduces soil compaction & increases crop yield.

Save Fuel

- Low Rolling resistance
- Decreased fuel consumption

Excellent Stability

- Uniform load distribution.
- Riding comfort & smoother ride over rough or uneven terrain.



Machineries



Tanker



Flotation Trailer

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	800/60R38 (SB)
Rec Rim	DW27B
Alternate Rim	-
PR & LI/SI	182 D
Section Width (mm)	818
Overall Diameter (mm)	1940
Static Load Radius (mm)	885
Rolling Circumference (mm)	5802
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	1	1.2	1.6	2	2.4	2.8	3.2
Static	8530	9590	11730	13430	15480	17550	19550

Mixed Application

km/h / bar	1	1.2	1.6	2	2.4	2.8	3.2
10	6680	7510	9180	10510	12110	13730	15300
25	5860	6590	8060	9230	10630	12060	13430
30	5600	6300	7700	8820	10160	11520	12840
40	5050	5670	6940	7940	9150	10380	11560
50	4490	5050	6170	7070	8140	9230	10290
65	3710	4170	5100	5840	6730	7630	8500