



TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



Salient Features & Benefits

TSB 110 – specially design for Tractors

Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance
- High Load Carrying Capacity
- Robust Nylon Casing.
- With stand high load in service.

Excellent Durability High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces which provides extended service life

Machineries



Tractor

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	7.5L-15
Rec Rim	6
Alternate Rim	-
PR & LI/SI	6 PR 93 AB
Section Width (mm)	210
Overall Diameter (mm)	745
Static Load Radius (mm)	341
Rolling Circumference (mm)	2228
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.3	2.5	2.7	3
Static	1650	1740	1830	1950

Mixed Application

km/h / bar	2.3	2.5	2.7	3
10	1100	1160	1220	1300
20	760	800	840	900
25	700	740	780	830
30	610	640	680	720
40	550	580	610	650