



## TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



### Salient Features & Benefits

#### TSB 110, specially design for Tractors

##### Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

##### High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

##### Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*6937*00
Tyre Size	5.00-15
Rec Rim	4.00E
Alternate Rim	4.5J
PR & LI/SI	6 PR 76 A8
Section Width (mm)	130
Overall Diameter (mm)	664
Static Load Radius (mm)	308
Rolling Circumference (mm)	1986
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	3.2	3.5	3.8	4.2
Static	1020	1080	1140	1200

### Mixed Application

km/h / bar	3.2	3.5	3.8	4.2
10	680	720	760	800
20	470	500	520	550
25	440	460	490	510
30	380	400	420	440
40	340	360	380	400