



TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



Salient Features & Benefits

TSB 110, specially design for Tractors

Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/17*6509*00
Tyre Size	5.50-16
Rec Rim	4.00E
Alternate Rim	4.25KA, 4.50E
PR & LI/SI	6 PR 82 A8
Section Width (mm)	150
Overall Diameter (mm)	713
Static Load Radius (mm)	330
Rolling Circumference (mm)	2133
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.2	2.6	3	3.9
Static	1020	1140	1230	1430

Mixed Application

km/h / bar	2.2	2.6	3	3.9
10	680	760	820	950
20	470	520	560	650
25	440	490	520	610
30	380	420	460	530
40	340	380	410	475