



## TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



### Salient Features & Benefits

#### TSB 110, specially design for Tractors

##### Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

##### High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

##### Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/17*6510*00
Tyre Size	6.00-16
Rec Rim	4.50E
Alternate Rim	4.00E, 4.25KA
PR & LI/SI	6 PR 85 A8
Section Width (mm)	159
Overall Diameter (mm)	739
Static Load Radius (mm)	341
Rolling Circumference (mm)	2211
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	2.7	3	3.3	3.6
Static	1290	1380	1470	1550

### Mixed Application

km/h / bar	2.7	3	3.3	3.6
10	860	920	980	1030
20	590	630	680	710
25	550	590	630	660
30	480	510	540	570
40	430	460	490	515