



TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



Salient Features & Benefits

TSB 110, specially design for Tractors

Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6938*00
Tyre Size	6.50-16
Rec Rim	4.00E
Alternate Rim	4.00E, 5.00F, 5.50F, 5K
PR & LI/SI	6 PR 88 A8
Section Width (mm)	173
Overall Diameter (mm)	761
Static Load Radius (mm)	350
Rolling Circumference (mm)	2276
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.5	2.7	3	3.3
Static	1440	1500	1590	1680

Mixed Application

km/h / bar	2.5	2.7	3	3.3
10	960	1000	1060	1120
20	660	690	730	770
25	610	640	680	720
30	530	560	590	620
40	480	500	530	560