



TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



Salient Features & Benefits

TSB 110, specially design for Tractors

Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/17*6511*00
Tyre Size	7.50-16
Rec Rim	5.50F
Alternate Rim	6LB
PR & LI/SI	8 PR 99 A8
Section Width (mm)	203
Overall Diameter (mm)	808
Static Load Radius (mm)	369
Rolling Circumference (mm)	2417
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.9	3.2	3.5	3.9
Static	1950	2070	2190	2330

Mixed Application

km/h / bar	2.9	3.2	3.5	3.9
10	1300	1380	1460	1550
20	900	950	1010	1070
25	830	880	930	990
30	720	770	810	860
40	650	690	730	775