



## TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



### Salient Features & Benefits

#### TSB 110, specially design for Tractors

##### Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

##### High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

##### Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

|                            |                       |
|----------------------------|-----------------------|
| ECE                        | E11*106R00/17*6534*00 |
| Tyre Size                  | 9.00-16               |
| Rec Rim                    | W8L                   |
| Alternate Rim              | 6.5F, 5.5F            |
| PR & LI/SI                 | 10 PR 111 A8          |
| Section Width (mm)         | 234                   |
| Overall Diameter (mm)      | 856                   |
| Static Load Radius (mm)    | 389                   |
| Rolling Circumference (mm) | 2561                  |
| Type                       | TT                    |

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

| km/h / bar | 3.2  | 3.5  | 3.8  | 4.2  |
|------------|------|------|------|------|
| Static     | 2820 | 2970 | 3120 | 3270 |

### Mixed Application

| km/h / bar | 3.2  | 3.5  | 3.8  | 4.2  |
|------------|------|------|------|------|
| 10         | 1880 | 1980 | 2080 | 2180 |
| 20         | 1300 | 1370 | 1440 | 1500 |
| 25         | 1200 | 1270 | 1330 | 1400 |
| 30         | 1040 | 1100 | 1150 | 1210 |
| 40         | 940  | 990  | 1040 | 1090 |