

TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



Salient Features & Benefits

TSB 110, specially design for Tractors

Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/17*6536*00
Tyre Size	10.00-16
Rec Rim	W8L
Alternate Rim	8LB
PR & LI/SI	10 PR 115 A8
Section Width (mm)	274
Overall Diameter (mm)	894
Static Load Radius (mm)	405
Rolling Circumference (mm)	2674
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.6	2.8	3.1	3.4
Static	3090	3240	3450	3650

Mixed Application

km/h / bar	2.6	2.8	3.1	3.4
10	2060	2160	2300	2430
20	1420	1490	1590	1680
25	1320	1380	1470	1560
30	1140	1200	1280	1350
40	1030	1080	1150	1215