



TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



Salient Features & Benefits

TSB 110, specially design for Tractors

Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/17*6538*00
Tyre Size	7.50-18
Rec Rim	5.50F
Alternate Rim	-
PR & LI/SI	8 PR 102 A8
Section Width (mm)	203
Overall Diameter (mm)	859
Static Load Radius (mm)	395
Rolling Circumference (mm)	2570
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.9	3.2	3.5	3.9
Static	2160	2280	2400	2550

Mixed Application

km/h / bar	2.9	3.2	3.5	3.9
10	1440	1520	1600	1700
20	990	1050	1100	1170
25	920	970	1020	1090
30	800	840	890	940
40	720	760	800	850