



TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



Salient Features & Benefits

TSB 110, specially design for Tractors

Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/17*6512*00
Tyre Size	6.00-19
Rec Rim	4.50E
Alternate Rim	-
PR & LI/SI	6 PR 89 A8
Section Width (mm)	165
Overall Diameter (mm)	815
Static Load Radius (mm)	379
Rolling Circumference (mm)	2438
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2.7	3	3.3	3.6
Static	1470	1560	1650	1740

Mixed Application

km/h / bar	2.7	3	3.3	3.6
10	980	1040	1100	1160
20	680	720	760	800
25	630	670	700	740
30	540	580	610	640
40	490	520	550	580