



## TSB 110 - Technical Specifications

Agriculture | Bias | F-2 | TT/TL | 5 Years



### Salient Features & Benefits

#### TSB 110, specially design for Tractors

##### Excellent Grip & Ease in Steering

- Enhanced Center Rib design.
- Optimum road contact for excellent steering performance.

##### High Load Carrying Capacity

- Robust Nylon Casing.
- With stand high load in service.

##### Excellent Durability, High-performance Tread compound.

- Offers resistance to cut & chip in all surfaces, which provides extended service life.

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/17*6539*00
Tyre Size	7.50-20
Rec Rim	5.50F
Alternate Rim	-
PR & LI/SI	8 PR 105 A8
Section Width (mm)	203
Overall Diameter (mm)	909
Static Load Radius (mm)	420
Rolling Circumference (mm)	2719
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	2.9	3.2	3.5	3.9
Static	2340	2490	2610	2780

### Mixed Application

km/h / bar	2.9	3.2	3.5	3.9
10	1560	1660	1740	1850
20	1080	1150	1200	1280
25	1000	1060	1110	1180
30	870	920	970	1030
40	780	830	870	925