

TDB 123 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 123, specially designed for agricultural applications.

Unbeatable Traction

- Unique 23 Degree Lug Design.
- Excellent Ground contact provides Excellent traction in operation.

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure.

Durability

- Special Tread compound
- Ensures Longer Life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6588*00
Tyre Size	23.1-26
Rec Rim	DW20
Alternate Rim	-
PR & LI/SI	12 PR 153 A8
Section Width (mm)	587
Overall Diameter (mm)	1605
Static Load Radius (mm)	720
Rolling Circumference (mm)	4801
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field operation with High Torque

km/h / bar	1.7
10	3910

Field operation with Low Torque

km/h / bar	1.7
10	5480
20	4490

Road Operation; Not high and Sustained Torque

km/h / bar	1.7
10	5480
20	4490
30	3910
40	3650
Static	8400