



TDB 123 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 123, specially designed for agricultural applications.

Unbeatable Traction

- Unique 23 Degree Lug Design.
- Excellent Ground contact provides Excellent traction in operation.

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure.

Durability

- Special Tread compound
- Ensures Longer Life.

Machinerics



Tractor

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

| | |
|----------------------------|------------------------|
| ECE | E11*106R00/21*10917*00 |
| Tyre Size | 23.1-30 |
| Rec Rim | 20 |
| Alternate Rim | - |
| PR & LI/SI | 14PR 157 AB |
| Section Width (mm) | 587 |
| Overall Diameter (mm) | 1707 |
| Static Load Radius (mm) | 771 |
| Rolling Circumference (mm) | 5105 |
| Type | TL |

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field operation with High Torque

| km/h / bar | 2 |
|------------|------|
| 10 | 4410 |

Field operation with Low Torque

| km/h / bar | 2 |
|------------|------|
| 10 | 6190 |
| 20 | 5070 |

Road Operation; Not high and Sustained Torque

| km/h / bar | 2 |
|------------|------|
| 10 | 6190 |
| 20 | 5070 |
| 30 | 4410 |
| 40 | 4125 |
| Static | 9490 |