



TDB 123 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 123, specially designed for agricultural applications.

Unbeatable Traction

- Unique 23 Degree Lug Design.
- Excellent Ground contact provides Excellent traction in operation.

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure.

Durability

- Special Tread compound
- Ensures Longer Life.

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*8206*00
Tyre Size	20.8-38
Rec Rim	W18A
Alternate Rim	-
PR & LI/SI	14 PR 159 A8
Section Width (mm)	528
Overall Diameter (mm)	1834
Static Load Radius (mm)	841
Rolling Circumference (mm)	5486
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field operation with High Torque

km/h / bar	2.3
10	4680

Field operation with Low Torque

km/h / bar	2.3
10	6560
20	5380

Road Operation; Not high and Sustained Torque

km/h / bar	2.3
10	6560
20	5380
30	4680
40	4375
Static	10060