



## TDB 123 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



### Salient Features & Benefits

**Tractor Drive Bias 123, specially designed for agricultural applications.**

#### Unbeatable Traction

- Unique 23 Degree Lug Design.
- Excellent Ground contact provides Excellent traction in operation.

#### Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure.

#### Durability

- Special Tread compound
- Ensures Longer Life.

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*6952*00
Tyre Size	20.8-38
Rec Rim	W18A
Alternate Rim	-
PR & LI/SI	8 PR 148 A8
Section Width (mm)	528
Overall Diameter (mm)	1834
Static Load Radius (mm)	841
Rolling Circumference (mm)	5486
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Field operation with High Torque

km/h / bar	1.3
10	3370

### Field operation with Low Torque

km/h / bar	1.3
10	4730
20	3870

### Road Operation; Not high and Sustained Torque

km/h / bar	1.3
10	4730
20	3870
30	3370
40	3150
Static	7250