



SSB 331 - Technical Specifications

Industrial & Construction | Bias | R-4 | TL | 5 Years

Salient Features & Benefits

Skid Steer Bias 331, specially designed for skid steer

High Traction and Excellent Self-Cleaning:

- Deep Tread with Optimized Spaced Lugs.
- Ensures superior traction on loose and rugged surfaces while improving self-cleaning capabilities for uninterrupted performance.

High Load-Carrying Capacity:

- Extra Strong Casing.
- Enables higher load handling across a variety of heavy-duty applications, enhancing overall operational efficiency.

Exceptional Cut and Chip Resistance:

- Special Tear and Cut Resistant Tread Compound.
- Provides outstanding durability in tough loading operations, minimizing damage and reducing downtime.

Rim and Wheel Protection:

- Reinforced Rim Guard.
- Protects the rim flange area against flats and wheel-related damage, increasing the service life of both tyre and wheel.



Machineries



Skid Steer Loader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/21*10826*00
Tyre Size	27X10-12 (250/75-12)
Rec Rim	8.00G
Alternate Rim	-
PR & LI/SI	14PR 152A2
Section Width (mm)	255
Overall Diameter (mm)	698
Static Load Radius (mm)	315
Rolling Circumference (mm)	2088
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	7
10	975
30	660