



## SSB 331 - Technical Specifications

Industrial & Construction | Bias | R-4 | TL | 5 Years

### Salient Features & Benefits

#### Skid Steer Bias 331, specially designed for skid steer

##### High Traction and Excellent Self-Cleaning:

- Deep Tread with Optimized Spaced Lugs.
- Ensures superior traction on loose and rugged surfaces while improving self-cleaning capabilities for uninterrupted performance.

##### High Load-Carrying Capacity:

- Extra Strong Casing.
- Enables higher load handling across a variety of heavy-duty applications, enhancing overall operational efficiency.

##### Exceptional Cut and Chip Resistance:

- Special Tear and Cut Resistant Tread Compound.
- Provides outstanding durability in tough loading operations, minimizing damage and reducing downtime.

##### Rim and Wheel Protection:

- Reinforced Rim Guard.
- Protects the rim flange area against flats and wheel-related damage, increasing the service life of both tyre and wheel.



## Machineries



Skid Steer Loader

**Standard:** ProductComponent.International Standards

## Dimensions ProductComponent.International Standards

ECE	E11*106R00/20*7789*00
Tyre Size	33X15.50-16.5
Rec Rim	12
Alternate Rim	-
PR & LI/SI	12PR 148A2
Section Width (mm)	394
Overall Diameter (mm)	840
Static Load Radius (mm)	383
Rolling Circumference (mm)	2522
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

## Load Capacity

km/h / bar		4.1
10		3150
30		2140