



MIB 405 - Technical Specifications

Industrial & Construction | Bias | L-2/G-2 | TL | 5 Years

Salient Features & Benefits

Multi Industrial Bias 405, specially designed for telehandler , grader and compact wheel loader application

Superior All-Terrain Traction

- Robust Tread Design with Deep Lugs
- Delivers excellent grip on soil, sand, gravel, and rocky terrain, ensuring confident operation across grading, earthmoving, and loading tasks.

Enhanced Stability & Operator Control

- High Contact Area with Balanced Footprint
- Promotes better ground stability and reduces slippage, especially on uneven surfaces, improving control and safety during operation.

Long Service Life in Tough Conditions

- High Abrasion-Resistant Compound
- Resists wear, cuts, and tearing, making the tyre ideal for heavy-duty cycles and extending its life in aggressive applications.

Reliable in Heat-Intensive Operations

- Durable Compound with Optimized Heat Dissipation
- Maintains performance in high-temperature and long-duration tasks minimizing the risk of blowouts and improving uptime.



Machineries



Telehandler



Compact Loader



Motor Grader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	15.5-25
Rec Rim	12
Alternate Rim	12DC
PR & LI/SI	12PR 168A2
Section Width (mm)	394
Overall Diameter (mm)	1277
Static Load Radius (mm)	583
Rolling Circumference (mm)	3820
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Grader Application

km/h / bar	2.3
40	2650

Loader/Telehandler Application

km/h / bar	4
10	5600
25	4480
30	4310