



## SCB 430 - Technical Specifications

Industrial & Construction | Bias | IND | TT / TL | 5 Years



### Salient Features & Benefits

**Smooth Compactor Bias 430, specially designed for pneumatic tyre roller**

#### Uniform Compaction and Stability

- High ground contact area.
- Provides uniform compaction of road belts and asphalt, ensuring consistent performance and improved operational stability.

#### Outstanding Heat Resistance

- Specially Formulated Heat-Resistant Compound.
- Performs reliably at high operating temperatures, making it ideal for continuous usage in hot-mix and asphalt-laying environments.

#### Extended Tyre Life

- Durable Compound Engineering.
- Enhances resistance to wear and thermal degradation, ensuring longer tyre life and reduced maintenance downtime.

## Machineries



Pneumatic Tyre Roller

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*8110
Tyre Size	9.5/65-15
Rec Rim	7
Alternate Rim	-
PR & LI/SI	6PR 118A2
Section Width (mm)	235
Overall Diameter (mm)	675
Static Load Radius (mm)	312
Rolling Circumference (mm)	2059
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar		3.3
10		1320
15		1060