



SCB 430 - Technical Specifications

Industrial & Construction | Bias | IND | TT / TL | 5 Years



Salient Features & Benefits

Smooth Compactor Bias 430, specially designed for pneumatic tyre roller

Uniform Compaction and Stability

- High ground contact area.
- Provides uniform compaction of road belts and asphalt, ensuring consistent performance and improved operational stability.

Outstanding Heat Resistance

- Specially Formulated Heat-Resistant Compound.
- Performs reliably at high operating temperatures, making it ideal for continuous usage in hot-mix and asphalt-laying environments.

Extended Tyre Life

- Durable Compound Engineering.
- Enhances resistance to wear and thermal degradation, ensuring longer tyre life and reduced maintenance downtime.

Machineries



Pneumatic Tyre Roller

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*8108
Tyre Size	10.5/80-16
Rec Rim	8
Alternate Rim	-
PR & LI/SI	6PR 129A2
Section Width (mm)	275
Overall Diameter (mm)	810
Static Load Radius (mm)	370
Rolling Circumference (mm)	2471
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar		4.5
10		1850
15		1500